

Indoor/Outdoor Enclosures

For information about NEMA and IP enclosure ratings, see page 799.

Corrosion-Resistant Washdown Fiberglass Enclosures (NEMA 4X) (Continued from previous page)

Contemporary Style

Streamlined design blends well in the office or the plant, indoors or out. Enclosures have a polyurethane-gasketed cover. Screws, hinges, and latches are stainless steel. Working depth (area available for component mounting) is approximately 0.7" less than overall depth. Opening size is approx. 1/2" less than overall height and width. Enclosures have four 1/4" mounting holes (or choose the optional flange-style mounting feet, sold separately, to aid installation). UL and C-UL listed. CSA certified. Also rated NEMA 12 for protection from oil/coolant dripping. Panels are aluminum.

Lift-Off Cover—Four captive screws hold cover in place.

Hinged Cover with Padlockable Latch—Have a hasp that accommodates 3/8" max. shackle dia. (padlock not included).

Hinged Cover with 1/4-Turn Latch—Latch is coin-slot style.

Hinged Cover with Window—Have two captive screws for closing. Window is acrylic.



Lift-Off Cover



Hinged Cover with 1/4-Turn Latch



Hinged Cover with Window

Overall Size, Ht. x Wd. x Dp.	ENCLOSURES				PANELS	
	Lift-Off Cover	Hinged Cover with Padlockable Latch	Hinged Cover with 1/4-Turn Latch	Hinged Cover with Window	Ht. x Wd.	Each
7.2" x 7.2" x 5.1"	74995K61	74995K71	74995K81	74995K91	4.9" x 4.9"	6917K12
9.2" x 7.2" x 5.1"	74995K62	74995K72	74995K82	74995K92	6.8" x 4.9"	6917K13
11.2" x 9.2" x 6.1"	74995K63	74995K73	74995K83	74995K93	8.8" x 6.9"	6917K14
13.2" x 11.2" x 6.6"	74995K64	74995K74	74995K84	74995K94	10.9" x 8.8"	6917K15
15.2" x 13.2" x 7.1"	74995K65	74995K75	74995K85	74995K95	12.9" x 10.9"	6917K16
						74995K99 Per Set

Mounting Feet (Set of 4)

74995K99 Per Set \$12.67

Corrosion-Resistant Washdown Polycarbonate Enclosures (NEMA 4X)

Highly impact and corrosion resistant, enclosures resist chipping and cracking under the toughest conditions. They're used as insulated electrical junction boxes, terminal wiring boxes, instrument housings, and electrical control boxes. They have internal studs for mounting DIN rail. All have a gray body. UL listed. Also rated NEMA 13 for protection from oil/coolant spraying. Steel panels for component mounting are sold separately.

With Lift-Off Cover

Cover screws are corrosion-resistant polyamide (unless noted). All have a polyurethane gasket (unless noted) and four 0.17" mounting holes. Back panel is galvanized steel. Working depth (area available for component mounting) is approximately 1/2" less than overall depth. Opening size is approximately 1/2" less than overall height and width.

To Order: Please specify opaque gray or transparent cover.

Overall Size, Ht. x Wd.	Shallow Enclosures		Deep Enclosures		Panels	
	Dp.	Each	Dp.	Each	Ht. x Wd.	Each
2" x 2"	1.6"	69945K91	—	—	1.8" x 1"	69945K94
2.6" x 2"	1.8"	69945K92	—	—	2.2" x 1"	69945K95
3.2" x 3.1"	2.6"	69945K93	—	—	2.8" x 2.2"	69945K96
5.1" x 3.1"	3"	69945K11	4.9"	69945K26	3.9" x 1.9"	69945K21
5.1" x 5.1"	3"	69945K12	4.9"	69945K27	3.9" x 3.9"	69945K22
6.7" x 3.1"	3.3"	69945K87	—	—	5.5" x 2.1"	69945K111
7.1" x 5.1"	3.9"	69945K13	5.9"	69945K28	5.8" x 3.9"	69945K23
7.1" x 7.1"	3.9"	69945K14	5.9"	69945K29	5.8" x 5.8"	69945K24
7.5" x 7.5"	5.1"	69945K15	7.1"	69945K39	5.8" x 5.8"	69945K53
9.1" x 3.1"	3.3"	69945K88	—	—	7.9" x 2.1"	69945K112
9.1" x 5.5"	3.7"	69945K89	—	—	7.3" x 3.7"	69945K113
11" x 7.5"	5.1"	69945K16	7.1"	69945K61	9.4" x 5.8"	69945K54
11" x 11"	5.1"	69945K18	7.1"	69945K63	9.4" x 9.4"	69945K56
15" x 7.5"	5.1"	69945K17	7.1"	69945K62	13.3" x 5.8"	69945K57
15" x 11"	5.1"	69945K19	7.1"	69945K64	13.3" x 9.4"	69945K55
22" x 11"	5.1"	69945K25	—	—	20.4" x 9.4"	69945K58
22" x 15"	—	—	7.1"	69945K97	20.4" x 13.3"	69945K98

◆ Has stainless steel cover screws. • Offered with opaque gray cover only. ■ Gasket is EPDM.

With Lift-Off Cover and Knockouts

Knockouts on top, bottom, and both sides allow fast and easy cable connecting. Cover has polyamide screws and EPDM gasket (unless noted). Enclosures have four 0.31" mounting holes. Working depth (area available for component mounting) is approximately 1/2" less than overall depth. Opening size is approximately 1/2" less than overall height and width. C-UL listed.

To Order: Please specify opaque gray or transparent cover.

Ht. x Wd.	Knockout Style (No.)		Shallow Enclosures		Deep Enclosures		Panels	
	Each Side	Top & Bottom	Dp.	Each	Dp.	Each	Ht. x Wd.	Each
5.1" x 3.1"	B(2)	A(1)	3"	7360K71	4.9"	7360K72	3.9" x 1.9"	69945K21
5.1" x 5.1"	B(2)	A(2)	3"	7360K73	4.9"	7360K74	3.9" x 3.9"	69945K22
7.1" x 5.1"	A(3)	B(2)	3"	7360K75	4.9"	7360K76	5.8" x 3.9"	69945K23
7.1" x 7.1"	B(3)	A(3)	3.9"	7360K77	5.9"	7360K78	5.8" x 5.8"	69945K24
10" x 7.1"	A(3), B(2)	B(3)	3.9"	7360K79	5.9"	7360K81	8.8" x 5.8"	7360K55

▲ Gasket is polyurethane.

With Hinged Cover

Offered with a padlockable latch (padlock not included; 3/8" max. shackle dia.) or a 1/4-turn key lock (includes one key). All have a polyamide hinge, EPDM cover gasket, and four mounting holes with M6 threads. Opening size is approximately 1/2" less than overall height and width.

To Order: Please specify opaque gray or transparent gray cover.

Overall Size, Ht. x Wd. x Dp.	ENCLOSURES				PANELS	
	Working Depth*	With Latch	With Key Lock	Ht. x Wd.	Each	
11.8" x 7.9" x 7.1"	6.6"	7335K21	7335K31	10.6" x 6.7"	7335K41	
11.8" x 11.8" x 7.1"	6.6"	7335K22	7335K32	10.6" x 10.6"	7335K42	
15.7" x 11.8" x 7.1"	6.6"	7335K23	7335K33	14.6" x 10.6"	7335K43	
19.7" x 15.7" x 7.9"	7.3"	7335K24	7335K34	18.5" x 14.6"	7335K44	
23.6" x 15.7" x 8.7"	8.1"	7335K25	7335K35	22.4" x 14.6"	7335K45	

*Area available for component mounting.



With Latch (Transparent Cover)




With Key Lock (Opaque Cover)



Shallow Enclosure (Opaque Cover)



Deep Enclosure (Transparent Cover)



Shallow Enclosure (Transparent Cover)