

Equipment Cooling Fan Accessories & Kits

Equipment Cooling Fan Guards, Filters, Power Cords, and Thermostat




Nickel-Plated Steel Fan Guard



Plastic Fan Guard



19155K47 Plastic Fan Guard



EMI/RFI Fan Guards

FILTER ASSEMBLIES



Guard



Media



Retainer

For use with equipment cooling fans on the previous page. **EMI/RFI fan guards** have stainless steel mesh screens in an aluminum frame to shield against electromagnetic and radio frequency interference.

Filter Assemblies—Consist of a plastic guard, plastic media retainer, and foam filter media. Original and replacement filters for 1.57" and 1.97" sizes can filter 30 ppi (particles per inch), 45 ppi for 3.62" and 4.69" sizes, and 60 ppi for 6.75" sizes.

Fan Guards and Filters—Sized to fit the equipment cooling fans on the previous page.

Mounting Holes, Ctr.-to-Ctr.	For Fan Size	Nickel-Plated Steel Fan Guards		Plastic Fan Guards		EMI/RFI Fan Guards		Filter Assemblies		Repl. Media for Filter Assemblies		
		Each	Each	Each	Each	Each	Each	Each	Pkg. Qty.	Per Pkg.		
1.11"	0.98" (25 mm) sq.	19155K89	\$0.69									
1.26"	1.57" (40 mm) sq.	19155K91	.85	19155K42	\$0.77			19155K2	\$1.67	5	19155K6	\$1.46
1.65"	1.97" (50 mm) sq.	19155K92	.95									
1.97"	2.36" (60 mm) sq.	19155K93	.96	19155K43	.80	19155K35	\$4.25	19155K3	1.88	5	19155K7	1.49
2.81"	3.15" (80 mm) sq.	19155K94	1.03	19155K44	.83	19155K36	4.56	19155K4	1.59	5	19155K8	1.69
3.25"	3.62" (92 mm) sq.	19155K95	1.08	19155K45	.87	19155K37	4.70	19155K22	2.20	5	19155K52	2.06
4.13"	4.69" (120 mm) sq.	19155K96	1.18	19155K46	1.02	19155K38	4.88	19155K23	2.70	5	19155K53	2.66
4.46"	5" (127 mm) sq.	19155K97	1.33			19155K39	5.26					
6.38"	6.75" (172 mm) dia.	19155K98	3.33	19155K47	1.85	19155K48	8.12	19155K5	3.61	5	19155K9	3.47
6.85"	10" (254 mm) dia.	19155K99	6.25									
8.19"	7.87" (200 mm) dia.	19155K27	5.14									
9.45"	8.86" (225 mm) sq.	19155K28	5.56									
9.45"	10.24" (260 mm) dia.	19155K28	5.56									
11.61"	11.02" (280 mm) dia.	19155K29	5.58									

QD (Quick-Disconnect) Power Cords

For equipment cooling fans with (QD) quick-disconnect terminals. UL listed and CSA certified.

Lg.	Straight Female Receptacle		45° Female Receptacle		90° Female Receptacle		Straight with Plain Wire Leads
	Each	Each	Each	Each	Each	Each	
With Plain Wire Leads							
24"	19155K34	\$2.00	19155K33	\$2.00	19155K31	\$2.00	
36"	19155K64	2.09	19155K63	2.09	19155K61	2.09	
With Two-Prong Plug							
36"	19155K71	4.25	19155K73	4.25	19155K72	4.25	
72"	19155K75	5.24	19155K77	5.24	19155K76	5.24	
With Three-Prong Plug							
24"	19155K56	9.47	19155K59	9.47	19155K67	9.47	
36"	19155K57	11.98	19155K65	11.98	19155K68	11.98	
72"	19155K58	11.84	19155K66	12.63	19155K69	12.63	



Thermostat

For use with equipment cooling fans on previous page. Control air temperatures in your enclosures. Set point range is 30° to 140° F. Has a SPST (single-pole, single-throw) switch rated 15 amps @ 120 VAC, 16 amps @ 250 VAC, and 10 amps at 12-24 VDC. Overall size is 2.37" Ht. x 1.31" Wd. x 1.55" Dp. Has screw-terminal connections.



19155K26 Each \$58.75

Equipment Cooling Fan Kits

Here's a no-hassle way to get everything you need to start cooling your equipment. Each kit includes an aluminum fan with plastic blades. Fans operate on 115 VAC, 50/60 Hz, single phase and have a 72" long cord with two-prong plug. Fans are UL recognized and cords are UL listed. **Kits with steel guard** include fan, cord, and nickel-plated steel fan guard. **Kits with filter assemblies** consist of fan, cord, and foam filter media sandwiched between a plastic guard and a plastic retainer. Media for 3.15" size filters 30 ppi (particles per inch) and 45 ppi for 4.69" and 5.91" sizes.



With Steel Guard



With Filter Assembly

Fan Size	cfm	Amps	Mounting Holes		With Steel Guard		With Filter Assembly			
			Ctr.-to-Ctr.	Size (Qty.)	Depth	Each	Depth	Each		
3.15" (80 mm) sq.	36	0.10	2.81"	0.17" (4)	1.72"	9191K1	\$41.25	1.88"	9191K4	\$42.36
4.69" (120 mm) sq.	65	0.10	4.13"	0.18" (4)	1.72"	9191K2	42.26	1.88"	9191K5	42.43
4.69" (120 mm) sq.	105	0.13	4.13"	0.18" (4)	1.72"	9191K3	42.71	1.88"	9191K6	43.04
5.91" (150 mm) sq.	240	0.25	6.38"	0.17" (2)	2.25"	9191K7	72.22	2.31"	9191K9	74.44
10" (254 mm) dia.	550	0.23	6.85"	0.18" (8)	3.7"	9191K8	102.78			

♡ Two sides are square; two are round.

Warmers for Equipment Cooling Fans

Warm the airflow from equipment cooling fans to maintain optimum temperatures in enclosures and remove moisture from the airflow. A sturdy aluminum frame protects the heating unit and radiates maximum heat. Easy to mount, just install in place of a finger guard. All have two 10" wire leads for connecting to a power source and are sized to fit the equipment cooling fans shown on the previous page. Have four 3/16" dia. mounting holes (mounting hardware not included). UL recognized.

Watts	Mounting Holes, Ctr.-to-Ctr.	120 VAC		230 VAC			
		Amps	Each	Amps	Each		
3.15" Sq. x 1.25" Dp.							
200	2.81"	1.67	20055K111	\$36.40	0.87	20055K311	\$36.40
400	2.81"	3.33	20055K112	36.40	1.74	20055K312	36.40
4.69" Sq. x 1.25" Dp.							
200	4.13"	1.67	20055K24	36.40	0.87	20055K44	36.40
400	4.13"	3.33	20055K25	36.40	1.74	20055K45	36.40
600	4.13"	5.00	20055K26	36.40	2.61	20055K46	36.40
800	4.13"	6.67	20055K27	36.40	3.48	20055K47	36.40

