






Item	<a href="#">Omega.com-PX429</a>	<a href="#">Omega.com-PX309</a>	<a href="#">Omega.com-PX329</a>	<a href="#">Omega.com-PX319</a>	<a href="#">EATON</a>
Connection Type	Twist-lock/Glass to metal	Cable	Twist-Lock	mini DIN	
Schematic					
Cost (\$)	\$540	~\$225	\$275	\$225	Free
Output (Vdc)	0-5Vdc	0-5Vdc	0-5Vdc	0-5Vdc	Either
Accuracy (%)	0.08%	0.25%	0.25%	0.25%	-
Resolution (psi)	4	25	25	25	-
Range (psi)	0-5,000	0-10,000	0-10,000	0-10,000	0-10,000
Life (cycles)	-	10,000,000	10,000,000	10,000,000	-
Operating Temp Range (oF)	-40 to 240	-40 to 185	-40 to 185	-40 to 185	-65 to 250
Response Time (sec)	-	<1 millisecond	<1 millisecond	<1 millisecond	-
Pressure Port	1/4 18 MNPT	1/4 18 MNPT	1/4 18 MNPT	1/4 18 MNPT	-
Electrical Connection	-	1.5m- 3 conductor	connector sold separate	mating connector included	-
Weight (grams)	-	155g	155g	155g	-
Output Wiring	4 pins	red/black/white	4 pins	6 pins	-
Excitation	-	Reverse Polarity/overvoltage	Reverse Polarity/overvoltage	Reverse Polarity/overvoltage	-